Technical data sheet proQuick clip, signal white

Item number: 2147370





Highly stressable clip for accepting plastic or metal electrical and sanitary pipes as well as the electrical installation pipe Quick pipe. Universal fastening options on walls, ceilings and steel constructions, both indoors and outdoors. Flexible clamping range of several millimetres. Tooless pipe mounting. Connectable to

each other to arrho 32 mm, also with the OBO Quick or Multi Quick clip. For variable distances and clip quantity mountable on a profile rail.











Polyamide

Master data

Item number	2147370
Туре	PQ-25 SWS
Description 1	proQuick clip
Manufacturer	OBO
Dimension	24-28mm
Colour	Signal white; RAL 9003
Material	Polyamide
Smallest sales unit	10
Unit of quantity	Piece
Weight	0.92 kg
Weight unit	kg/100 pc.

Technical data sheet


proQuick clip, signal white

Item number: 2147370



Dimensions 4,2x12





Technical data			
	Expandable	yes	
	Number of cables/pipes	1	
	Fastening type	Screw hole	
	Breaking load	0.85 kN	
	Closed	yes	
	Halogen-free	yes	
	With inlay	no	
	Nominal size	25-28	
	Snap system	yes	
	Pipe/cable diameter, max.	28 mm	
	Pipe/cable diameter, min.	24 mm	
	Clamping range D, max.	28 mm	
	Clamping range D, min.	24 mm	
	Permitted temperature range, max.	60 °C	
	Permitted temperature range, min.	-15 °C	
	UV-resistant	yes	