

Technical data sheet

UDHOME2 floor socket, without floor covering recess, freely equippable, stainless steel, decorative plate: angelhair
Item number: 7368261



Square floor socket for use in dry-care cavity and screed floors in indoor areas. Installation housing with pre-marked insertion openings for pipes (M20/M25). Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 100 mm, the height-adjustment range 35 mm. Frame and cover made of stainless steel and visible in the floor covering. Cover with Angelhair decorative plate. Empty housing for up to 2 Modul 45® devices in the mounting support and 2 data sockets in the optional data technology support. The load-bearing capacity of 15 kN is only guaranteed when in an unused state.



Master data


| | |
|---------------------|-----------------------|
| Item number | 7368261 |
| Description 1 | Floor socket |
| Description 2 | unequipped, Angelhair |
| Manufacturer | OBO |
| Dimension | 140x140x110 |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 220 kg |
| Weight unit | kg/100 pc. |

Technical data sheet

UDHOME2 floor socket, without floor covering recess, freely equippable, stainless steel, decorative plate: angelhair
Item number: 7368261



Dimensions



| | |
|--------|--------|
| Length | 140 mm |
| Width | 140 mm |
| Height | 100 mm |

Technical data

| | |
|---|-----------------------------|
| Number of installable devices | 2 |
| Version for | Square |
| Cable outlet version | Swivellable cord outlet |
| Equipment | Empty housing |
| Floor covering protection frame | no |
| Floor care | Dry |
| Seal installation option | no |
| Application when used | 6.101.1 Dry floor care |
| Application when unused | 6.101.1 Dry floor care |
| Floor height, max. | 135 mm |
| Floor height, min. | 100 mm |
| Suitable for raised floor installation | yes |
| Suitable for screed-flush closed underfloor ducts | no |
| Suitable for screed-covered underfloor ducts | no |
| Suitable for cavity floor installation | yes |
| Suitable for wet care | no |
| Suitable for underfloor ducts | no |
| Device support to accept mounting boxes | no |
| With floor covering recess | no |
| Nominal size for device installation units | 2 |
| Standard | EN 50085-2-2 |
| Frame version | Floor covering contact edge |
| Protection rating (IP) when used | IP20 |
| Protection rating (IP) when unused | IP40 |
| Protection rating IK code | IK10 |
| Heavy-duty version | no |
| Vertical load, small area | to 3,000 N |

Technical data sheet

UDHOME2 floor socket, without floor covering recess, freely equippable, stainless steel, decorative plate: angelhair
Item number: 7368261



Technical data

| | |
|-------------------|--------|
| Approvals | VDE |
| Opening mechanism | Handle |